

# Preamplifier Accessories and Cables

## **AA0023**

### **Cable for B&K 2669 preamplifier**

3 m cable for use from B&K 2669 to 7-pin LEMO 1B series male.

## **AA0042**

### **Flat cable for windows**

½ m flat preamplifier cable for use in architectural acoustics.

## **AF0008**

### **Adapter for ¼" preamplifier and ½" microphone**

An inline barrel adapter for using ¼" preamplifiers with ½" microphones. Included with Preamplifier Type 26AB.

## **AG0001**

### **Adapter for 7-pin LEMO to B&K**



The AG0001 is an adapter for a 7-pin LEMO connector and a traditional 7-Pin B&K microphone input connector.

## **AL0002**

### **Tripod Adapter for microphones**

The AL0002 is an adapter for mounting ½" or ¼" preamplifiers with microphones on tripods with a standard ¼" W thread.



## **AL0003**

### **Tripod Adapter for microphones**

The AL0003 is an adapter with a swivel head for mounting ½" or ¼" preamplifiers with microphones on tripods with a standard ¼" W thread.

## **AL0006**

### **Tripod**

A versatile and robust tripod for measurement set-ups and cameras. Its main features are: • Standard mounting thread (¼" whitworth) • Practical carrying handle • Crank-adjusted centre column • Rubber feet with adjustable spikes • Adjustable tripod legs with locks • Locking of tripod-legs cross brace • Max. height 161 cm • Retracted 65 cm • Weight 1.6 kg.

## **AL0008**

### **Tripod Adapter for microphones**

The AL0008 is an adapter for mounting ½" preamplifiers with microphones on tripods with a standard ¼" W thread.

## **GR0010**

### **Adapter for ¼" preamplifier and ½" microphone**

An inline stub adapter for using ¼" preamplifiers with ½" microphones. Included with Preamplifier Types 26AC, 26AL and 26CB.

## **PA0017**

### **Cable Drum**

The PA0017 is a cable drum for approximately 100 m of standard or high quality microphone cable.

## **RA0011**

### **Gooseneck**

The RA0011 is a 20 cm flexible gooseneck with 7-pin LEMO connectors for use with preamplifiers with integrated 7-pin LEMO connectors such as Types 26AK, 26AJ and 26AB. For example, it can be mounted between the preamplifier and a sound level meter in order to reduce reflections.

## **RA0037**

### **Adapter for Microdot input to a ¼" preamplifier.**

The RA0037 is an adapter for using a Microdot input to a standard ¼" preamplifier such as the Type 26AC. Useful when a high input impedance is required for transducers such as hydrophones and accelerometers.

## Preamplifier Accessories and Cables

---

### **RA0062**

#### **20pF Preamplifier-input Adapter for 1/2" preamplifiers**

The RA0062 is a 20 pF input adapter for 1/2" preamplifiers. One end screws on to a 1/2" preamplifier and the other end has a BNC input connector. This enables connecting a signal generator to the input of the preamplifier. Short circuiting the BNC input results only in loading the preamplifier by 20 pF.

### **RA0080**

#### **6pF Preamplifier-input adapter for 1/4" microphones**

The RA0080 is a 6 pF input adapter for 1/4" preamplifiers. One end screws on to a 1/4" preamplifier and the other end has a Microdot input connector. This enables connecting a signal generator to the input of the preamplifier. Short circuiting the Microdot input results only in loading the preamplifier by 6 pF.

#### **Adjustable, high-quality, stainless-steel tripod adapters**

RA0096: for 1/4" microphones/preamplifiers

RA0093: for 1/2" microphones/preamplifiers

RA0094: for microphone arrays

Angular adjustment: 180° in steps of 45°

#### **Adapter cables for B&K**

AA0024: 2 m adapter cable from B&K female socket to 7-pin LEMO 1B series male.



AA0041: 1.5 m adapter cable from B&K male to BNC plug

#### **Extension cables for Preamplifier Type 26AA**

AA0006: 2 m cable 4-pin LEMO 0B to 4-pin LEMO 0B (for Type 50AI)

AA0007: 2 m cable 4-pin LEMO 0B to 7-pin LEMO 1B

#### **Preamplifier extension cables with 7 pin LEMO to 7 pin LEMO**

Extension cables for preamplifiers with 7 pin LEMO connectors are available in two versions: High quality (HQ) and standard quality (SQ). The high-quality version are cables with an outer sleeve of Polyurethane for maximum wear resistance and Teflon-coated inner sleeves for maximum insulation and temperature stability.

Standard lengths:

Cable length	SQ	HQ
3 m	N/A	AA0008
10 m	AA1009	AA0009
30 m	AA1012	AA0012
100 m	AA1014	AA0014

Custom lengths:

XXm	AA1020/XX	AA0020/XX
-----	-----------	-----------