



VIEW A-A
SCALE 4/1

1. CABLE MAXIMUM OPERATING TEMPERATURE 250°

ALL PARTNUMBER LETTER SUFFIXES ARE TO BE INTERPRETED AS FOLLOWS:
 I.E. - 107-0000-01H
 M - MACHINED ONLY (UNPLATED) G - MATERIAL HAS BEEN GRAINED
 P - PLATED/PAINATED S - MATERIAL HAS BEEN SAWCUT
 H - HEAT TREATED E - ENVIRONMENTAL TEST

EXCEPT AS OTHERWISE NOTED
 ALL DIMENSIONS IN INCHES
 TOLERANCE: .XX± ± .25
 SURFACE FINISH EXCEPT AS NOTED ✓
 BREAK EDGES TO DEBURR
 RADIUS OR CHAMFER
 1 THESE DIAS TO T.I.R.
 FILLETS - MAX RAD.

		CHATSORTH, CA.			
		SCALE 2/1	REV	DATE	ECN
DATE 7/2/96		PART NO. MODEL 6428AXX			
DRAWN D.Z.	CHECKED N.C.	MATERIAL			
APPROVED		NEXT ASSEMBLY		USED ON	
TITLE OUTLINE DRAWING MINI 4 PIN, PLUG TO (3) BNC					DWG NO. 127-6428A
					SHEET 1 OF 1